New Model Available August 2005

New Ultra-Portable LCD Projector

PLC-XU70

- **XGA resolution**
- **1500 ANSI lumens**
- **Monitor output –** Switchable 2nd Data Input
- **Electronic keystone correction**
- **Eco Mode**
- **Standard Lens 1.8 - 2.15:1**
- **PIN Code Security**
- **Capacitor Back Up**
- **Manual Zoom & Focus**
- **Weighs only 2.4kg**

Model name	PLC-XU70
Panel	0.6 inch TFT p-Si x 3
No. of pixels	1024 x 768
Projection lamp	180W UHP Lamp
Brightness (typical)	1500 ANSI lumens
Uniformity	85% (corner to centre)
Contrast ratio	400:1
Up-Down ratio	9:1, Digital Keystone ± 20° vertical
Projection lens Throw ratio Screen size	F 1.65 – 1.81, f=22.5 – 27mm 1.8 – 2.15:1 40”-300”
AV Signal	Input: Composite (RCA), Component(D-Sub15), S-Video(DIN4) Stereo (RCAx2)
Color systems	PAL / SECAM / NTSC / NTSC4.43 / PAL-M/N
PC Signal	Input: D-sub15 x 1 Audio input: Mini-Jack (Stereo) for Computer Input Audio output: Mini-Jack (Stereo) variable output Output: RGB (D-Sub15), switchable 2nd data input
Control Port	Serial x 1 (RS-232C), USB type B x 1
Computer compatibility	UXGA/ SXGA/ XGA/ SVGA/ VGA/ MAC
Scanning frequency	H-sync 15-100kHz, V-sync 50-100Hz, Dot Clock 140MHz
Sound output	1.0W mono
Voltage	100V-240V AC (auto voltage)
Dimensions(W x H x D)	295 x 70 x 208 mm
Weight	2.4kg